

PRIME TIME WC Waterbased Wood Floor Cleaner

Limpiador De Madera Del Piso De Waterbased



Availability:

 Packaging
 Item #

 2-2.5 Gal.:
 107756

 Pail/ 5 Gal.:
 107748

 Drum/ 55 Gal.:
 102782



DESCRIPTION

This product is designed to thoroughly clean wood floors without leaving any residue. Excellent for use prior to applying waterbased coatings- as conventional floor cleaners leave a detergent residue that can cause adhesion and wear problems. This waterbased wood floor cleaner is also designed for daily tacking or damp mopping to remove soils and excess mop treatment.



PRIME TIME WC Waterbased Wood Floor Cleaner





FEATURES

- Ideal tack rag cleaner
- Versatile
- Leaves no residue behind

BENEFITS

- Removes soils and excess mop treatment
- Eliminates adhesion issues

AREAS OF USE:

- Colleges
- Wood Floors
- High schools
- Arenas
- Gvmnasiums

Odor:

Color:

Blue

Fragrance Free

pH:

10.5 - 12.0

Recommended Dilution:

SPECIFICATIONS:

1:6 - 1:64

Base:

Detergent with solvent

Viscosity:

Water thin

Foam:

Low

Solubility:

Complete

Emulsification:

Good

Rinsability:

Excellent

Flash Point:

120°F

Storage/Stability:

2 years

Weight Per Gallon:

8.19lbs/gal.

Freeze/Thaw Stability:

Keep from freezing

- Can be used as cleaner or for finish prep

DIRECTIONS

FOR DAILY MAINTENANCE BY TACKING:

Add 12 to 16 ounces of concentrate, depending on soil conditions, to a mop bucket and fill with water. Soak 3 to 4 towels in solution until they are thoroughly wet. Wring towels out thoroughly and place one towel flat on floor. Place push broom in middle of towel, pulling front half of towel over top of the broom, and tack rag the floor. Repeat procedure as towel gets

FOR DAILY MAINTENANCE BY DAMP MOPPING:

Add 12 ounces of concentrate to mop bucket and fill with water. Wring out and damp mop floor in usual manner. Do not over wet or flood floor with product.

FOR CLEANING NEWLY SCREENED FLOORS PRIOR TO FINISHING:

Add 12 to 16 ounces of concentrate, depending on soil conditions, to a mop bucket and fill with water. Soak 3 to 4 towels in solution until they are thoroughly wet. Follow directions above and tack the floor. This procedure must be repeated after each screening. After the final screening, the floor should be tack ragged a second time with fresh solution and clean towels prior to application of the finish.

WARNING

HAZARD STATEMENTS

Causes eye irritation. Causes mild skin irritation.

Combustible liquid

PRECAUTIONARY STATEMENTS

Wash thoroughly after handling.
Do not get in eyes, on skin, or on clothing.
Keep out of reach of children.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves and eye protection.

FIRST AID:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

In case of fire: Use dry chemical, alcohol-resistant foam for extinction.

Store in closed container in an area inaccessible to children

Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities. Store in a well-ventilated place. Keep container tightly closed. SPILL/LEAK

Avoid walking in product. Wipe up or otherwise flush small spills to sanitary

Dispose of contents/container in accordance with local, state and federal regulations

Isopropanol - (67-63-0), Ethylene glycol butyl ether - (111-76-2), Sodium Lauryl Sulfate - (151-21-3), Dye - (N/A), Water - (7732-18-5)

1048 Stinson Drive, Reading PA 19605 Phone: 1-800-548-4568

www.miscoproducts.com