

Universal Socks #GCSO1210 - 3" x 12', 10 socks/package



Super-absorbent Cellulose Socks soak up more than one gallon for every four feet!

- **Very Thirsty Socks:** A single 12' Sock can absorb more than three gallons of oils, coolants, solvents or water, making it a true top performer.
- **Contain and Soak Up Leaks or Spills:** Ideal for surrounding spilled fluids or wrapping around leaky machines. Easy and convenient to put into place. Contain spills to keep fluids from spreading into larger areas and becoming slippery hazards. Very flexible to conform around machine bases and offer a snug fit with no seepage.
- **Color-Coded:** Color-coding helps you visually identify the right sorbent for your needs. Gray signifies Universal sorbency.

GCSO1210 Specifications

Dimensions:	ext. dia. 3" x 12' L
Shipping Dimensions:	21" W x 25.5" L x 21.5" H
Sold as:	10 socks per package
Color:	Gray
Composition:	Cellulose Filler/Polypropylene Sleeve
Absorbency:	Up to 34 gal. per package
Absorbency per:	Up to 3.4 gal. per sock
# per Pallet:	16
Incinerable:	Yes
Ship Class:	150

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 3.7m L
Shipping Dimensions:	53.3cm W x 64.8cm L x 54.6cm H
Absorbency:	Up to 128.7 L per package
Absorbency per:	Up to 12.9 L per sock

GCSO1210 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com