

Universal Pillows #GPIL1010 - 10" x 10", 40 pillows/package



Whether in a SpillTech® Pillow in a Pan or on its own, a Universal Pillow absorbs high-volume leaks and spills of oils, coolants, solvents or water.

- **Perfectly Sized Replacement Saves You Money:** Economical Pillow drops right into your Pillow in a Pan to replace a saturated absorbent without the cost of a new Pan.
- **Pillows Absorb Fluids in Tight Spaces:** Pillows are easy to place in hard-to-reach areas — use under machines and leaky hydraulic hoses or wedge in corners cramped for space.
- **One Product for a Variety of Uses:** Pulls liquids from the floor like a sock. Catches leaks like a pan. Absorbs spills like a pad. It's one versatile product that works for many different jobs.
- **Absorb Large Quantities ... Quickly:** Ideal for spill response. Easy to toss into action. Pillow's large surface area speeds the absorption process and shortens the overall response time.
- **Color-Coded:** Color-coding helps you visually identify the right sorbent for your needs. Grunge-hiding Gray signifies universal sorbency for oils, coolants, solvents and water. Note: These items are not compatible with sulfuric acid.

GPIL1010 Specifications

Dimensions:	10" W x 10" L
Shipping Dimensions:	24" W x 16" L x 11.5" H
Sold as:	40 pillows per package
Color:	Gray
Composition:	Poly Blend
Absorbency:	Up to 30 gal. per package
Absorbency per:	Up to 96 oz. per pillow
# per Pallet:	35
Incinerable:	Yes
Ship Class:	150

Metric Equivalent Specifications

Dimensions:	25.4cm W x 25.4cm L
Shipping Dimensions:	61cm W x 40.6cm L x 29.2cm H
Absorbency:	Up to 113.6 L per package
Absorbency per:	Up to 2.8 L per pillow

GPIL1010 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

29 CFR 1910.22(a)(2) - Floors in your workplace should be, "maintained in a clean and, so far as possible, a dry condition."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com