

## Universal Tuff Rug™ Roll #MR2069 - 33" x 150', 1 roll/package



Tough StitchBonded mat handles heavy wear and foot traffic.

- Strongest mat stands up to heavy abuse — leave down much longer than regular mat and save money
- Place in busy aisles, walkways and workstations where slippery floors are a concern
- Zigzag stitching adds extra strength so mat won't fray or come apart
- Absorbent polypropylene fibers pull in liquids to keep floors dry
- Absorbs most common industrial liquids: oils, coolants, solvents and water

### MR2069 Specifications

|                             |                           |
|-----------------------------|---------------------------|
| <b>Dimensions:</b>          | 33" W x 150' L            |
| <b>Shipping Dimensions:</b> | 14" W x 34" L x 14" H     |
| <b>Sold as:</b>             | 1 roll per package        |
| <b>Color:</b>               | Gray                      |
| <b>Composition:</b>         | Polypropylene             |
| <b>Absorbency:</b>          | Up to 23 gal. per package |
| <b># per Pallet:</b>        | 24                        |
| <b>Basis Weight:</b>        | HeavyWeight               |
| <b>Incinerable:</b>         | Yes                       |
| <b>Ship Class:</b>          | 150                       |

### Metric Equivalent Specifications

|                             |                                |
|-----------------------------|--------------------------------|
| <b>Dimensions:</b>          | 83.8cm W x 46m L               |
| <b>Shipping Dimensions:</b> | 35.6cm W x 86.4cm L x 35.6cm H |
| <b>Absorbency:</b>          | Up to 87.1 L per package       |

## MR2069 Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

29 CFR 1910.22(a)(2) - Floors in your workplace should be, "maintained in a clean and, so far as possible, a dry condition."

29 CFR 1910.107(g)(2) - OSHA requires spraying areas to be "kept as free from the accumulation of deposits of combustible residues as practical."

29 CFR 1910.107(b)(3) - If floors in a spray booth or work area are combustible, they "shall be covered with noncombustible material of such character as to facilitate the safe cleaning and removal of residues."

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)

Safety Data Sheet (SDS)



Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)