

# 4-Drum Steel Pallet #QTX1212 - 50" x 50" x 13", 1 each/package



These 14-gauge galvanized steel containment pallets are the strongest on the market!

- Each pallet has a 250 PSF loading capacity and a 60 gallon sump capacity
- Noncombustible pallets meet spill control and containment requirements and regulations
- Pallets will not melt under fire exposure or fail from normal material handling activities
- 100% leak-free tested
- Removable grating

### **QTX1212 Specifications**

Dimensions:	50" W x 50" L x 13" H
Shipping	50" W x 50" L x 13" H
Dimensions:	
Sold as:	1 per package
Color:	Gray
Composition:	14 Gauge Steel
Load Capacity UDL:	4340 lbs. per package
Sump Capacity:	68 gal. per package
# per Pallet:	13
Incinerable:	No
Ship Class:	92.5

## **Metric Equivalent Specifications**

Dimensions:	127cm W x 127cm L x 33cm H
Shipping	127cm W x 127cm L x 33cm H
Dimensions:	
Load Capacity UDL:	1968.6 kg per package
Sump Capacity:	257.4 L per package







Email: sales@spilltech.com

5440 McGinnis Village Place, Ste. 102 • Alpharetta GA 30005 © 2018 SpillTech Environmental Corporation. All rights reserved.

# **QTX1212 Technical Information**

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

#### **Regulations and Compliance:**

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

### **Technical Documents:**

(Available at spilltech.com)

Product Data Sheet (PDS)





Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

5440 McGinnis Village Place, Ste. 102 • Alpharetta GA 30005 © 2018 SpillTech Environmental Corporation. All rights reserved.