



**SPILLTECH**

**SpillTech**  
5440 McGinnis Village Place  
Suite 102  
Alpharetta, GA 30005  
Phone: 1-800-228-3877  
Fax: 1-800-872-3764  
www.spilltech.com

## **MATERIAL SAFETY DATA SHEET**

### **SECTION I: IDENTIFICATION OF PRODUCT**

PRODUCT NAME: RagRug Matting  
CHEMICAL FAMILY: Olefin

#### **Company Profile:**

SpillTech  
Brookley Industrial Complex  
1627 O'Donoghue Street  
Mobile, AL 36615

**Customer Service Telephone Number:** 1-800-228-3877

**Technical Information Telephone Number:** 1-251-694-0102 ext.121

### **SECTION II: HAZARDOUS INGREDIENTS**

<b><u>INGREDIENTS</u></b>	<b><u>PERCENT</u></b>	<b><u>CAS NUMBER</u></b>	<b><u>OSHA PEL</u></b>	<b><u>ACGIH TLV</u></b>
Polyester Fibers	var. ~ 75%	N/A	N/A	N/A
Acrylic Fiber	var. ~ 25%	N/A	N/A	N/A

### **SECTION III: HAZARDS IDENTIFICATION**

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0  
FLAMMABILITY: 1  
REACTIVITY: 0

\* Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

**SECTION IV: FIRST AID MEASURES**

EYE CONTACT: Use eyewash, consult physician if accompanied by pain or irritation.  
SKIN CONTACT: N/A  
INHALATION: N/A  
INGESTION: N/A

**SECTION V: FIRE FIGHTING MEASURES**

FLASH POINT: N/A  
AUTO IGNITION: N/A no explosion hazard  
FLAMMABLE LIMITS: N/A Matting has been *lightly* treated with flame retardant\*  
FIRE EXTINGUISHING MEDIA: Water, Foam, CO2, Dry Chemical  
SPECIAL FIRE FIGHTING PROCEDURES: Standard procedures for Class A fires  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Overheated or molten material may burn with dense smoke. Avoid inhalation of vapors.  
Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

*\* Matting has been lightly treated with a spray-on flame retardant. However, internal test show that this amount is not high enough to inhibit burning or classify this material as "self-extinguishing"*

**SECTION VI: ACCIDENTAL RELEASE MEASURES**

If material is not contaminated, return to proper package for use. If material is contaminated, please in proper container for disposal. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding  
Product is fabric made from polyolefin fibers and yarn and the roll may be very heavy. Use caution in the even of spill on uneven ground. Use suitably rated lifting equipment in the event a roll needs to be moved.

**SECTION VII: HANDLING AND STORAGE**

Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons. Adequate ventilation is required to remove decomposition products when temperature exceeds melting point. Avoid contact with melted product.  
Store away from oxidizing materials in a cool, dry place. Do not store near smoking areas. Fiber scraps and cuttings should be kept away from floors and aisle ways.  
No special handling needed for uncontaminated product. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

**SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT**

RESPIRATORY PROTECTION: None Required  
VENTILATION: None Required  
PROTECTIVE GLOVES: None Required  
EYE PROTECTION: Safety glasses with side shields are recommended as a good practice for industrial safety.  
OTHER PROTECTIVE EQUIPMENT (SPECIFY): None Required

**SECTION IX: PHYSICAL DATA**

APPEARANCE AND ODOR:	Gray and multi-colored fibers & virtually odor free
SPECIFIC GRAVITY:	0.915
BOILING POINT (C):	Not Applicable
MELTING POINT (C):	191° C (375° F)
SOLUBILITY IN WATER:	Insoluble
PERCENT VOLATILE BY VOLUME:	N/A
EVAPORATION RATE:	N/A
VAPOR PRESSURE (mm Hg):	N/A
VAPOR DENSITY (Air = 1):	N/A

**SECTION X: TRANSPORT INFORMATION**

DOT CLASSIFICATION: Non Hazardous

**SECTION XI: WASTE XI DISPOSAL METHOD**

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

**SECTION XII: PREPARATION**

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

**DATE ISSUED:** April 29, 2002

**REVIEWED (no changes):** February 2014

**PREPARED BY:** SpillTech, Telephone Number: 1-800-228-3877.