

Oil-Only 50-Gallon Wheeled Spill Kit #SPKO-CAN-WD - Absorbs up to 45.9 Gallons



Roll your kit right to oily spills up to 45.9 gallons

- Kit contains everything you need to respond to a spill of oily liquids
- Prepacked container provides easy access to contents
- Includes socks to stop spreading spills, mats and pillows to absorb liquids and safety equipment like goggles, gloves and coveralls
- Bold "Spill Kit" lettering for quick identification
- Bright yellow 50-gallon overpack with wheels to roll to the spill
- Hinged lid provides easy access
- Temporary disposal bags for easier cleanup
- Tamperproof seal helps prevent pilfering of spill response supplies







Email: sales@spilltech.com

5440 McGinnis Village Place, Ste. 102 • Alpharetta GA 30005 © 2018 SpillTech Environmental Corporation. All rights reserved.

SPKO-CAN-WD Specifications

Dimensions:
Shipping
Dimensions:
Sold as:
Absorbency:
per Pallet:
Incinerable:
Ship Class:
Includes:

23.5" W x 29" L x 36.75" H
1 per package
Up to 45.9 gal. per package
2
No
175
100 - 15" x 19" White Oil-Only
HeavyWeight Defender Pads
(WPB100H)
6 - 3" x 4' White Oil-Only Sorbent
Socks (WSO430)
4 - 3" X 12' White Oil-Only Sorbent
Socks (WSO1210)
1 - Emergency Response GuideBook
(A-EGB)
4 - 30" X 60" Yellow Disposal Bags &
Ties (A-DISPBAG)
2 - Safety Goggles (A-GOG)
2 - Pair Nitrile Gloves (A-GLV-NIT)
2 - Coveralls (A-TYVEK-L)
1 - 3" x 5" Vinyl Spill Kit Label (A-
KITLABEL)
1 - 29" x 23.5" x 36.75" Yellow 50-
Gallon Wheeled Container (A50CAN-
WD)
6 - 6" x 2" TamperProof Seals (A-
SEAL)
3 - 28oz Shaker SuperSorb (SS1)
2 - 56/pkg Wipers (A-WIPER)

23.5" W x 29" L x 36.75" H

Metric Equivalent Specifications

Dimensions:	59.7cm W x 73.7cm L x 93.3cm H
Shipping	59.7cm W x 73.7cm L x 93.3cm H
Dimensions:	
Absorbency:	Up to 173.7 L per package







Email: sales@spilltech.com

SPKO-CAN-WD Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)







Email: sales@spilltech.com

5440 McGinnis Village Place, Ste. 102 • Alpharetta GA 30005 © 2018 SpillTech Environmental Corporation. All rights reserved.