

Universal 50-Gallon Wheeled OverPack Salvage Drum Spill Kit #SPKU-50-WD - Absorbs up to 45.7 Gallons



Be prepared for fast response with a SpillTech® Universal OverPack Salvage Drum Spill Kit!

- **Quick Response is Key:** Spills happen no matter how hard you try to avoid them. Forklifts knock over drums, tanks are punctured and transporters leak and drip. It is important to have the right sorbents on-hand when these spills occur to eliminate the slip-and-fall hazard. A quick response is the first order of business — and your best weapon — in the fight against spills. SpillTech® Spill Kits are packed with quality SpillTech® Products to help you clean up fast and comply with regulations.
- **The Sorbents You Need Are All Inside:** Includes a variety of sorbents to handle spills of oils, coolants, solvents or water; pre-packed in an X-rated DOT-approved 50-Gallon OverPack Salvage Drum. Self-contained Kit stores sorbent products for easy access as needed for spill control; saves time when quick response is necessary. Twist-on, double-wall lid with closed-cell gasket provides sealed and secure closure to protect sorbents from moisture, dirt and damage. Rust- and corrosion-free 100% polyethylene is durable to withstand rough handling. All-in-one design for easy maneuvering; two attached wheels and built-in handle mean no dolly or material handling equipment is needed.
- **Customized for You:** Don't see what you're looking for We can customize a Spill Kit to your exact specifications, including the container, its contents and accessories, with no upcharge! Contact your local Distributor for details.

SPKU-50-WD Specifications

Dimensions:	ext. dia. 28.75" x 45.5" H
Shipping Dimensions:	28.75" W x 45.5" L x 28.75" H
Sold as:	1 per package
Composition:	N/A
Absorbency:	Up to 45.7 gal. per package
# per Pallet:	4
Incinerable:	No
Ship Class:	150
Includes:	100 - 15" x 19" Gray Universal HeavyWeight SonicBonded Pads (GPB100H) 6 - 3" x 4' Gray Universal Sorbent Socks (GCSO430) 4 - 18" x 18" Gray Universal Sorbent Pillows (GPIL1818) 1 - 7" Epoxy Putty Stick (A-EPOXY) 1 - 6" Glow Light Stick (A-LIGHTSTICKS) 1 - Emergency Response GuideBook (A-EGB) 5 - 18" X 30" Yellow Disposal Bags & Ties (A-DISP BAG-SM) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KITLABEL) 1 - 24.5" x 39.5" Yellow 50-Gallon Wheeled OverPack (1H2/X125/S) (A50OVER-WD) 6 - 6" x 2" TamperProof Seals (A-SEAL)

Metric Equivalent Specifications

Dimensions:	ext. dia. 73cm x 115.6cm H
Shipping Dimensions:	73cm W x 115.6cm L x 73cm H
Absorbency:	Up to 173 L per package



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

SPKU-50-WD Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com