

4-Drum Ultra-Spill Deck® #ULT1072 - 52" x 52" x 5.75" 1/package



Low-profile, modular Spill Decks let you design and create a containment system that meets your specific needs.

- 1-, 2- and 4-Drum Ultra-Spill Decks® can be used alone or are easily connected together with Bulkhead Fittings (ULT1073) and T-Strips (ULT1131) to allow a virtually unlimited number of customized configurations
- Bulkhead fittings lock Spill Decks together while allowing spills to flow between Decks; can help you meet containment regulations depending on the size of container stored and the total sump capacity of the Deck system
- All-polyethylene construction meets a wide range of chemical compatibility needs
- Low height offers safe and convenient loading/unloading of drums
- Ideal for collecting hazardous waste, storing virgin chemicals or batteries, dispensing from drums and more
- Optional Loading Ramp (ULT1089) provides added drum handling safety and convenience

ULT1072 Specifications

Dimensions:	52" W x 52" L x 5.75" H
Shipping	52" W x 52" L x 7" H
Dimensions:	
Sold as:	1 per package
Color:	Yellow
Composition:	100% Polyethylene
Load Capacity UDL:	6000 lbs. per package
Sump Capacity:	44 gal. per package
# per Pallet:	10
Incinerable:	No
Ship Class:	125

Metric Equivalent Specifications

Dimensions:	132.1cm W x 132.1cm L x 14.6cm H
Shipping	132.1cm W x 132.1cm L x 17.8cm H
Dimensions:	
Load Capacity UDL:	2721.6 kg per package
Sump Capacity:	166.5 L per package



Online: spilltech.com



Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

5440 McGinnis Village Place, Ste. 102 • Alpharetta GA 30005 © 2018 SpillTech Environmental Corporation. All rights reserved.

ULT1072 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)







Email: sales@spilltech.com