

## 2-Drum Ultra-Spill Deck® #ULT1086 - 52" x 26" x 5.75" 1/package



Low-profile, modular Spill Decks let you design and create a containment system that meets your specific needs.

- 1-, 2- and 4-Drum Ultra-Spill Decks® can be used alone or are easily connected together with Bulkhead Fittings (ULT1073) and T-Strips (ULT1131) to allow a virtually unlimited number of customized configurations
- Bulkhead fittings lock Spill Decks together while allowing spills to flow between Decks; can help you meet containment regulations depending on the size of container stored and the total sump capacity of the Deck system
- All-polyethylene construction meets a wide range of chemical compatibility needs
- Low height offers safe and convenient loading/unloading of drums
- Ideal for collecting hazardous waste, storing virgin chemicals or batteries, dispensing from drums and more
- Optional Loading Ramp (ULT1089) provides added drum handling safety and convenience

### ULT1086 Specifications

|                             |                         |
|-----------------------------|-------------------------|
| <b>Dimensions:</b>          | 26" W x 52" L x 5.75" H |
| <b>Shipping Dimensions:</b> | 26" W x 52" L x 7" H    |
| <b>Sold as:</b>             | 1 per package           |
| <b>Composition:</b>         | 100% Polyethylene       |
| <b>Load Capacity UDL:</b>   | 3000 lbs. per package   |
| <b>Sump Capacity:</b>       | 22 gal. per package     |
| <b># per Pallet:</b>        | 20                      |
| <b>Incinerable:</b>         | No                      |
| <b>Ship Class:</b>          | 125                     |

### Metric Equivalent Specifications

|                             |                               |
|-----------------------------|-------------------------------|
| <b>Dimensions:</b>          | 66cm W x 132.1cm L x 14.6cm H |
| <b>Shipping Dimensions:</b> | 66cm W x 132.1cm L x 17.8cm H |
| <b>Load Capacity UDL:</b>   | 1360.8 kg per package         |
| <b>Sump Capacity:</b>       | 83.3 L per package            |

## ULT1086 Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)



**SpillTech**

Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)