

# 4-Drum Spill Pallet #ULT1113 - with drain



Store drums and other leak- or spill-prone containers on this Pallet to help you comply with regulations.

- Low Profile and Heavy Load Capacity: 4-Drum Pallet has a low profile and can hold up to 3,000 lb.
- Meets Containment Requirements: Provides a 66-gallon sump to protect and help keep you in compliance — in the event of a small leak or complete drum failure.
- Strong, Durable and Long Lasting: All-polyethylene construction makes the Pallet light-weight and resistant to chemicals. Won't rust or corrode. Black color disguises dirt and wear and tear — keeps the Pallet looking good.
- Removable Grate Makes It Easy to Get to the Sump: Equipped with a polyethylene grate that can be easily removed for quick access to sump area. Drain plug makes it simple to empty.

# **ULT1113 Specifications**

**Dimensions:** 53" W x 53" L x 11.75" H **Shipping** 53" W x 53" L x 11.75" H

**Dimensions:** 

Sold as: 1 per package

Color: Black

Composition: Polyethylene

Recycled Content: 90% Post-Industrial Recycled

Polyethylene Grates

**Load Capacity UDL:** 3000 lbs. per package **Sump Capacity:** 66 gal. per package

# per Pallet: 7
Incinerable: No
Ship Class: 200

# **Metric Equivalent Specifications**

**Dimensions:** 134.6cm W x 134.6cm L x 29.8cm H **Shipping** 134.6cm W x 134.6cm L x 29.8cm H

**Dimensions:** 

Load Capacity UDL: 1360.8 kg per package
Sump Capacity: 249.8 L per package



Online: spilltech.com

Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

## **ULT1113 Technical Information**

#### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### **Regulations and Compliance:**

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

#### **Technical Documents:**

(Available at **spilltech.com**)
Product Data Sheet (PDS)
Chemical Compatibility (CCG)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com