

Ultra-IBC Hard Top® #ULT1162 - Without Drain 1/package



Comply with regulations while storing IBC tanks outdoors.

- Upper roll-top cover and swing out lower doors combine to allow easy and convenient access to IBC
- Low-profile containment pallet allows safe material handling and dispensing
- Forkliftable, lockable, all-polyethylene design will not rust or corrode
- Also available with drain plug (ULT1161) to let you empty sump without relocating stored containers

ULT1162 Specifications

Dimensions: 62" W x 64.5" L x 96" H **Shipping** 62" W x 65" L x 96" H

Dimensions:

Sold as: 1 per package

Color: Yellow

Composition:100% PolyethyleneLoad Capacity UDL:8500 lbs. per packageSump Capacity:360 gal. per package

per Pallet: 1
Incinerable: No
Ship Class: 250

Metric Equivalent Specifications

Dimensions: 157.5cm W x 163.8cm L x 2.4m H **Shipping** 157.5cm W x 165.1cm L x 2.4m H

Dimensions:

Load Capacity UDL: 3855.6 kg per package **Sump Capacity:** 1362.6 L per package



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

ULT1162 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com