

# 1-Drum Ultra-Spill Deck® #ULT1321 - 26" x 26" x 5.75" 1/package



Low-profile, modular Spill Decks let you design and create a containment system that meets your specific needs.

- 1-, 2- and 4-Drum Ultra-Spill Decks® can be used alone or are easily connected together with Bulkhead Fittings (ULT1073) and T-Strips (ULT1131) to allow a virtually unlimited number of customized configurations
- Bulkhead fittings lock Spill Decks together while allowing spills to flow between Decks; can help you meet containment regulations depending on the size of container stored and the total sump capacity of the Deck system
- All-polyethylene construction meets a wide range of chemical compatibility needs
- Low height offers safe and convenient loading/unloading of drums
- Ideal for collecting hazardous waste, storing virgin chemicals or batteries, dispensing from drums and more
- Optional Loading Ramp (ULT1089) provides added drum handling safety and convenience

## **ULT1321 Specifications**

**Dimensions:** 26" W x 26" L x 5.75" H **Shipping** 27" W x 35" L x 7" H

Dimensions:

Sold as: 1 per package

Color: Yellow

Composition: 100% Polyethylene
Load Capacity UDL: 3000 lbs. per package
Sump Capacity: 11 gal. per package

# per Pallet: 20
Incinerable: No
Ship Class: 200

## **Metric Equivalent Specifications**

**Dimensions:** 66cm W x 66cm L x 14.6cm H **Shipping** 68.6cm W x 88.9cm L x 17.8cm H

**Dimensions:** 

Load Capacity UDL: 1360.8 kg per package
Sump Capacity: 41.6 L per package



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

## **ULT1321 Technical Information**

#### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### **Regulations and Compliance:**

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

#### **Technical Documents:**

(Available at spilltech.com)

Product Data Sheet (PDS)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com