

## Ultra-550 Containment Sump #ULT2820 - With Drain 1/package



Sump offers secondary containment for 500- and 550-gallon tanks.

- Eliminate costly spills while storing fuels, oils and other hazardous liquids
- 100% polyethylene construction will not rust or corrode; provides superior chemical and weather resistance
- Drain plug lets you easily remove collected liquid
- Offers the best protection for non-monitored containment sites

### ULT2820 Specifications

<b>Dimensions:</b>	62.25" W x 87" L x 32.75" H
<b>Shipping Dimensions:</b>	60" W x 89" L x 34" H
<b>Sold as:</b>	1 per package
<b>Color:</b>	Black
<b>Composition:</b>	100% Polyethylene
<b>Sump Capacity:</b>	605 gal. per package
<b># per Pallet:</b>	6
<b>Incinerable:</b>	No
<b>Ship Class:</b>	300

### Metric Equivalent Specifications

<b>Dimensions:</b>	158.1cm W x 2.2m L x 83.2cm H
<b>Shipping Dimensions:</b>	152.4cm W x 2.3m L x 86.4cm H
<b>Sump Capacity:</b>	2289.9 L per package

## ULT2820 Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)



**SpillTech**

Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)