



Store hazardous drums safely outdoors with pumps and funnels in place!

- Extra headspace easily accommodates rotary drum pumps and large conical funnels
- Low-profile containment pallet positions drum tops at a safe, convenient level to pour wastes into funnels or use drum pumps
- 100% polyethylene construction will not rust or corrode
- Roll-top covers can be easily lifted from waist height to access drum tops; no need to reach near ground level
- Swing out lower doors provide full access to drums for loading and unloading
- Lockable with a standard padlock; safely lifted by forklift with drums in place
- Optional loading ramp (ULT0676) with non-slip surface stores neatly inside when not in use — even when loaded with four 55gallon drums
- Also available with drain plug (ULT9637) to let you empty sump without relocating stored containers

ULT9636 Specifications

Spill

| Dimensions: | 62" W x 64.5" L x 79" H |
|--------------------|-------------------------|
| Shipping | 64" W x 66" L x 84" H |
| Dimensions: | |
| Sold as: | 1 per package |
| Color: | Yellow |
| Composition: | 100% Polyethylene |
| Load Capacity UDL: | 9000 lbs. per package |
| Sump Capacity: | 75 gal. per package |
| # per Pallet: | 1 |
| Incinerable: | No |
| Ship Class: | 250 |

Metric Equivalent Specifications

| Dimensions: | 157.5cm W x 163.8cm L x 2m H |
|--------------------|--------------------------------|
| Shipping | 162.6cm W x 167.6cm L x 2.1m H |
| Dimensions: | |
| Load Capacity UDL: | 4082.4 kg per package |
| Sump Capacity: | 283.9 L per package |



Online: spilltech.com



Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

5440 McGinnis Village Place, Ste. 102 • Alpharetta GA 30005 © 2018 SpillTech Environmental Corporation. All rights reserved.

ULT9636 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS)



Online: spilltech.com



Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com