

HazMat Poly Blend Socks #YSO1210 - 3" x 12', 10 socks/package



When hazardous liquids spill, use HazMat Sorbents for quick, efficient response. These poly blend-filled Socks contain and soak up acids, bases and unknown fluids fast.

YSO1210 Specifications

Dimensions:	ext. dia. 3" x 12' L
Shipping	22" W x 24" L x 18.25" H
Dimensions:	
Sold as:	10 socks per package
Color:	Yellow Speckled Filler/Yellow Sleeve
Composition:	Poly Blend
Recycled Content:	100% Post-Industrial Recycled Poly
	Blend Filler
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 2.5 gal. per sock
# per Pallet:	16
Incinerable:	Yes
Ship Class:	150

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 3.7m L
Shipping	55.9cm W x 61cm L x 46.4cm H
Dimensions:	
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 9.5 L per sock



Online: spilltech.com Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other)



Email: sales@spilltech.com

5440 McGinnis Village Place, Ste. 102 • Alpharetta GA 30005 © 2018 SpillTech Environmental Corporation. All rights reserved.

YSO1210 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)







Email: sales@spilltech.com